

Gas ultrasonic flowmeter for permanent installation


Transmitter for permanent outdoor wall or pipe mounting

Features

- Exact and highly reliable bidirectional clamp-on flow measurement of operational and standard volume flow rates as well as mass flow rates
- Installation and start-up do not require any pipe work nor any process interruptions
- High measurement accuracy even at very low as well as very high flow rates and independent of the flow direction (bidirectional)
- Automatic loading of calibration data and transducer recognition
- Bidirectional communication and support of common bus technologies (Profibus PA, Foundation Fieldbus, HART, Modbus, BACnet, M-Bus)
- Advanced self-diagnosis and possibilities for event-based triggering of data recording for the supervision and control of critical processes
- Transmitter and transducers for use in hazardous areas are available
- Transmitter and transducers are separately calibrated (traceable to national standards)
- Transducers available for a wide range of inner pipe diameters and fluid temperatures
- The measurement is zero point stable, drift free and independent of the pipe material as well as the process pressure (> 3 bar on steel pipes; no minimum pressure for plastic pipes) and the process fluid
- The measurement system also precisely measures wet gas flow rates up to 5 % LVF (liquid volume fraction)

Applications

- Chemical industry
- Petrochemical industry
- Oil and gas industry
- Manufacturing industries



FLUXUS G721**-.****A



FLUXUS G721**-.****S




Variotix C

Function	3
Measurement principle	3
Calculation of volumetric flow rate	3
Calculation of mass flow rate	4
Calculation of standard volumetric flow rate	4
Calculation of gas energy flow rate (NGE)	4
Number of sound paths	5
Transmitter	6
Technical data	6
Dimensions	8
2" pipe mounting kit	9
Terminal assignment	10
Transducers	11
Transducer selection	11
Technical data	14
Transducer mounting fixture	24
Coupling materials for transducers	26
Damping material (optional)	27
Damping mats	27
Damping coat	28
Connection systems	29
Junction box	31
Technical data	31
Dimensions	32
2" pipe mounting kit	32
Clamp-on temperature probe (optional)	33
Technical data	33
Fixation	35
Junction box	35

Function

Measurement principle


The transducers are mounted on the pipe which is completely filled with the fluid. The ultrasonic signals are emitted alternately by a transducer and received by the other. The physical quantities are determined from the transit times of the ultrasonic signals.



As the fluid where the ultrasound propagates is flowing, the transit time of the ultrasonic signal in flow direction is shorter than the one against the flow direction.

The transit time difference Δt is measured and allows the flowmeter to determine the average flow velocity along the propagation path of the ultrasonic signals. A flow profile correction is then performed in order to obtain the area averaged flow velocity, which is proportional to the volumetric flow rate.

The integrated microprocessors control the entire measuring cycle. The received ultrasonic signals are checked for measurement usability and evaluated for their reliability. Noise signals are eliminated.



Calculation of volumetric flow rate

$$\dot{V} = k_{Re} \cdot A \cdot k_a \cdot \frac{\Delta t}{2 \cdot t_y}$$

where

- \dot{V} - volumetric flow rate
- k_{Re} - fluid mechanics calibration factor
- A - cross-sectional pipe area
- k_a - acoustical calibration factor
- Δt - transit time difference
- t_y - average of transit times in the fluid

Calculation of mass flow rate

The mass flow rate is calculated from the operating density and the volumetric flow rate:

$$\dot{m} = \rho \cdot \dot{V}$$

The operating density of the fluid is calculated as the function of pressure and temperature of the fluid:

$$\rho = f(p, T)$$

where

- ρ - operating density
- p - fluid pressure
- T - fluid temperature
- \dot{m} - mass flow rate
- \dot{V} - volumetric flow rate

Calculation of standard volumetric flow rate

The standard volumetric flow rate can be selected as physical quantity. It is calculated with the following formula:

$$\dot{V}_N = \dot{V} \cdot \frac{p}{p_N} \cdot \frac{T_N}{T} \cdot \frac{1}{K}$$

where

- \dot{V}_N - standard volumetric flow rate
- \dot{V} - operating volumetric flow rate
- p_N - standard pressure (absolute value)
- p - operating pressure (absolute value)
- T_N - standard temperature in K
- T - operating temperature in K
- K - compressibility coefficient of gas: ratio of the compressibility factors of the gas at operating conditions and at standard conditions Z/Z_N

The operational pressure p and the operational temperature T of the fluid will be entered directly as fixed values into the transmitter.

or:

If inputs are installed (optional), pressure and temperature can be measured by the customer and fed in the transmitter.

Calculation of gas energy flow rate (NGE)

For natural gas with changing composition (NGE fluid data sets), the Natural Gas Engine (NGE) can be used to calculate the gas energy flow rate:

$$\Phi = HHV_V \cdot \dot{V}_N = HHV_m \cdot \dot{m}$$

$$HHV_m = \rho_N \cdot HHV_V$$

where

- Φ - gas energy flow rate
- \dot{V}_N - standard volumetric flow rate
- \dot{m} - mass flow rate
- HHV_V - higher heating value, volume-related
- HHV_m - higher heating value, mass-related
- ρ_N - normalised density

Number of sound paths

The number of sound paths is the number of transits of the ultrasonic signal through the fluid in the pipe. Depending on the number of sound paths, the following methods of installation exist:

- **reflection arrangement**

The number of sound paths is even. The transducers are mounted on the same side of the pipe. Correct positioning of the transducers is easy.


- **diagonal arrangement**

The number of sound paths is odd. The transducers are mounted on opposite sides of the pipe. In the case of a high signal attenuation by the fluid, pipe and coatings, diagonal arrangement with 1 sound path will be used.


The preferred method of installation depends on the application. While increasing the number of sound paths increases the accuracy of the measurement, signal attenuation increases as well. The optimum number of sound paths for the parameters of the application will be determined automatically by the transmitter.

As the transducers can be mounted with the transducer mounting fixture in reflection arrangement or diagonal arrangement, the number of sound paths can be adjusted optimally for the application.


Reflection arrangement, number of sound paths: 2




Diagonal arrangement, number of sound paths: 3



Diagonal arrangement, number of sound paths: 1





Diagonal arrangement, number of sound paths: 1, negative transducer distance



a - transducer distance

Transmitter

Technical data

		FLUXUS G721**-NN0*A	FLUXUS G721**-NN0*S	FLUXUS G721**-E20*S
				
design		standard field device nonEx	field device with stainless steel housing nonEx	field device with stainless steel housing zone 2
measurement				
measurement principle		transit time difference correlation principle		
flow velocity	m/s	0.01...35, depending on pipe diameter		
repeatability		0.15 % MV ±0.005 m/s		
fluid		all acoustically conductive gases, e.g. nitrogen, air, oxygen, hydrogen, argon, helium, ethylene, propane		
temperature compensation		corresponding to the recommendations in ANSI/ASME MFC-5.1-2011		
measurement uncertainty		see metrological certificate		
transmitter				
power supply		• 100...230 V/50...60 Hz or • 20...32 V === or • 11...16 V ===		
power consumption	W	< 15		
number of measuring channels		1, optional: 2		
damping	s	0...100 (adjustable)		
measuring cycle	Hz	100...1000 (1 channel)		
response time	s	1 (1 channel), option: 0.02		
housing material		aluminum, powder coated	stainless steel 316L (1.4404)	
degree of protection		IP66	IP66	IP66
dimensions	mm	see dimensional drawing		
weight	kg	5.4	5.1	
fixation		wall mounting, optional: 2" pipe mounting		
ambient temperature	°C	-40...+60 (< -20 °C without operation of the display)	-40...+60 (< -20 °C without operation of the display)	-40...+60 (< -20 °C without operation of the display)
display		128 x 64 dots, backlight		
menu language		English, German, French, Spanish, Dutch, Russian, Polish, Turkish, Italian		
explosion protection				
• TR TS				
marking		-	-	2Ex nA nC [ic] IIC T4 Gc Ex tb IIIC T120 °C Db от -40 °C до +60 °C пыль: от -40 °C до +50 °C
certification		-	-	ATEX TC RU C-DE.BH02.B.00644
measuring functions				
physical quantities		operating volumetric flow rate, standard volumetric flow rate, mass flow rate, flow velocity, gas energy flow rate (NGE)		
totaliser		volume, mass, gas energy (NGE)		
calculation functions		average, difference, sum (2 measuring channels necessary)		
diagnostic functions		sound speed, signal amplitude, SNR, SCNR, standard deviation of amplitudes and transit times		
communication interfaces				
service interfaces		measured value transmission, parametrisation of the transmitter: • USB ² • LAN ²		
process interfaces		max. 1 option: • RS485 (ASCII sender) • Modbus RTU ³ • BACnet MS/TP • M-Bus • HART ³ • Profibus PA ³ • FF H1 ³ • Modbus TCP ³ • BACnet IP	max. 1 option: • RS485 (ASCII sender) • Modbus RTU ³ • BACnet MS/TP • M-Bus • HART ³ • Profibus PA ³ • FF H1 ³ • Modbus TCP ³ • BACnet IP	max. 1 option: • RS485 (ASCII sender) • Modbus RTU ³ • BACnet MS/TP • HART ³ • Profibus PA ³ • FF H1 ³ • Modbus TCP ³ • BACnet IP

² outside the explosive atmosphere (housing cover open)

³ with inputs and including parametrisation of the transmitter


		FLUXUS G721**-NN0*A	FLUXUS G721**-NN0*S	FLUXUS G721**-E20*S
accessories				
data transmission kit		USB cable		
software		• FluxDiagReader: reading of measured values and parameters, graphical presentation • FluxDiag (optional): reading of measurement data, graphical presentation, report generation, parametrisation of the transmitter		
data logger				
loggable values		all physical quantities, totalised physical quantities and diagnostic values		
capacity		max. 800 000 measured values		
outputs				
		The outputs are galvanically isolated from the transmitter.		
number		on request		
• switchable current output				
		All switchable current outputs are jointly switched to active or passive.		
range	mA	4...20 (3.2...22)		
accuracy		0.04 % MV ±3 µA		
active output		R _{ext} < 350 Ω		
passive output		U _{ext} = 8...30 V, depending on R _{ext} (R _{ext} < 1 kΩ at 30 V)		
• HART				
range	mA	4...20		
accuracy		0.1 % MV ±15 µA		
active output		U _{int} = 24 V, R _{ext} < 500 Ω		
passive output		U _{ext} = 10...24 V \pm , depending on R _{ext} (R _{ext} < 1 kΩ at 24 V)		
• voltage output				
range	V	0...1 or 0...10		
accuracy		0...1 V: 0.1 % MV ±1 mV 0...10 V: 0.1 % MV ±10 mV		
internal resistance		R _{int} = 500 Ω		
• frequency output				
range	kHz	0...5		
optorelay		24 V/4 mA, R _{int} = 66.5 Ω		
• binary output				
optorelay		26 V/100 mA		
Reed relay		48 V/100 mA, R _{int} = 22 Ω		
binary output as alarm output				
• functions		limit, change of flow direction or error		
binary output as pulse output				
• functions		mainly for totalising		
• pulse value	units	0.01...1000		
• pulse width	ms	optorelay: 1...1000 Reed relay: 80...1000		
inputs				
		The inputs are galvanically isolated from the transmitter.		
number		max. 4, on request		
• temperature input				
type		Pt100/Pt1000		
connection		4-wire		
range	°C	-150...+560		
resolution	K	0.01		
accuracy		±0.01 % MV ±0.03 K		
• current input				
accuracy		0.1 % MV ±10 µA		
active input		U _{int} = 24 V, R _{int} = 50 Ω, P _{int} < 0.5 W, not short-circuit proof		
• range	mA	0...20		
passive input		R _{int} = 50 Ω, P _{int} < 0.3 W		
• range	mA	-20...+20		
• voltage input				
range	V	0...1		
accuracy		0.1 % MV ±1 mV		
internal resistance		R _{int} = 1 MΩ		
• binary input				
switching signal		5...30 V, 1 mA		
functions		• reset of the measured values • reset of the totalisers • stop of the totalisers • activation of the measuring mode for highly dynamic flows		

² outside the explosive atmosphere (housing cover open)


³ with inputs and including parametrisation of the transmitter

Dimensions

72_****A**




72_****S**




2" pipe mounting kit

72-****A**




order code:
ACC-PE-*721-/PMK4

72-****S**



order code:
ACC-PE-*721-/PMK6

Terminal assignment



power supply ¹								
terminal				connection (AC)		connection (DC)		
PE				earth		earth		
N(-)				neutral		-		
L(+)				phase		+		
transducers								
transducer cable (transducers *****8*, ****L*), extension cable				transducer cable (transducers *****52)				
measuring channel A		measuring channel B		transducer	measuring channel A		measuring channel B	
terminal	connection	terminal	connection		terminal	connection		
AV	signal	BV	signal		↑	X_AV	X_BV	SMB connector
AVS	shield	BVS	shield		↕	X_AR	X_BR	SMB connector
ARS	shield	BRS	shield					
AR	signal	BR	signal					
outputs ^{1, 2}								
terminal		connection		terminal	connection		communication interface	
P1+...P4+ P1-...P4-		current output, voltage output, frequency output, binary output (Reed relay), HART (P1)		A+	signal +		• RS485 ¹ • Modbus RTU ¹ • BACnet MS/TP ¹ • M-Bus ¹ • Profibus PA ¹ • FF H1 ¹	
				B-	signal -			
P5a...P7a P5b...P7b		binary output (optorelay)		S	shield			
				USB	type B Hi-Speed USB 2.0 Device		• service (FluxDiag/ FluxDiagReader)	
				LAN	RJ45 10/100 Mbps Ethernet		• service (FluxDiag/ FluxDiagReader) • BACnet IP • Modbus TCP	
analog inputs ^{1, 2}								
		temperature probe		passive sensor		active sensor		
terminal		direct connection	connection with extension cable	connection		connection		
T1a...T4a		red	red	not connected		not connected		
T1A...T4A		red/blue	grey	-		+		
T1b...T4b		white/blue	blue	+		not connected		
T1B...T4B		white	white	not connected		-		
S1, S3		shield	shield	not connected		not connected		
binary inputs ^{1, 2}								
terminal								
P1+ _ P2+ P1- _ P2-								

¹ cable (by customer):
 - e.g. flexible wires, with insulated wire ferrules, wire cross-section: 0.25...2.5 mm²
 - outer diameter of the cable (*721**..*****S with ferrite nut): max. 7.6 mm


² The number, type and terminal assignment are customised.

Transducers

Transducer selection


Step 1a

Select a Lamb wave transducer:



Step 1b

If the pipe wall thickness is not in the range of the Lamb wave transducers, select a shear wave transducer:




Step 2


inner pipe diameter d dependent on the flow velocity v of the fluid in the pipe

The transducers are selected from the characteristics (see next page). Lamb wave transducers are selected from the left column, shear wave transducers from the right column.


Lamb wave transducers: If the values d and v are not in the range, the diagonal arrangement with 1 sound path may be used, i.e. the same characteristics can be used with doubling the inner pipe diameter. If the values are still not in the range, shear waves transducers regarding the pipe wall thickness have to be selected in step 1b.

Lamb wave transducer¹


GLF




GLG




GLH




GLK




GLM




GLP




GLQ

shear wave transducer¹


GSG




GSK



GSM



GSP



GSQ

¹ inner pipe diameter and max. flow velocity for a typical application with natural gas, nitrogen, oxygen in reflection arrangement with 2 sound paths (Lamb wave transducers)/1 sound path (shear wave transducers)

Step 3

min. fluid pressure

Lamb wave transducer			
transducer or- der code	fluid pressure ¹ [bar]		
	metal pipe		plastic pipe
	min.	min. extended	min.
GLF	15	10	1
GLG	15	10	1
GLH	15	10	1
GLK	15 (d > 120 mm) 10 (d < 120 mm)	10 (d > 120 mm) 3 (d < 120 mm)	1
GLM	10 (d > 60 mm) 5 (d < 60 mm)	3 (d < 60 mm)	1
GLP	10 (d > 35 mm) 5 (d < 35 mm)	3 (d < 35 mm)	1
GLQ	10 (d > 15 mm) 5 (d < 15 mm)	3 (d < 15 mm)	1

shear wave transducer			
transducer or- der code	fluid pressure ¹ [bar]		
	metal pipe		plastic pipe
	min.	min. extended	min.
GSG	30	20	1
GSK	30	20	1
GSM	30	20	1
GSP	30	20	1
GSQ	30	20	1

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

d - inner pipe diameter

Example


step					
1	pipe wall thickness	mm	14.3	8.6	38
	selected transducer		GLG or GLH	GLH or GLK	GS
2	inner pipe diameter	mm	581	96.8	143
	max. flow velocity	m/s	15	30	30
	selected transducer		GLG	GLK	GSK
3	min. fluid pressure	bar	20	15	40
	selected transducer		GLG	GLK	GSK

Step 4

for the technical data of the selected transducer see page 14 et seqq.

Technical data

Shear wave transducers (zone 2 - nonEx, TS)

order code		GSG-N**TS/**	GSK-N**TS/**	GSM-N**TS/**	GSP-N**TS/**	GSQ-N**TS/**
technical type		G(DL)G1N52	G(DL)K1N52	G(DL)M2N52	G(DL)P2N52	G(DL)Q2N52
transducer frequency	MHz	0.2	0.5	1	2	4
fluid pressure ¹						
min. extended	bar	metal pipe: 20				
min.	bar	metal pipe: 30, plastic pipe: 1				
inner pipe diameter d ²						
min. extended	mm	180	60	30	15	7
min. recommended	mm	220	80	40	20	10
max. recommended	mm	900	300	150	50	22
max. extended	mm	1100	360	180	60	30
pipe wall thickness						
min.	mm	11	5	2.5	1.2	0.6
material						
housing		PEEK with stainless steel cover 304 (1.4301), ***-****/OS: 316L (1.4404)				
contact surface		PEEK				
degree of protection		IP67				
transducer cable						
type		1699				
length	m	5		4		3
length (***-****/LC)	m	9 (not for *L**** with ***-*E***)				
dimensions						
length l	mm	129.5	126.5	64		40
width b	mm	51	51	32		22
height h	mm	67	67.5	40.5		25.5
dimensional drawing						
weight (without cable)	kg	0.47	0.36	0.066		0.016
pipe surface temperature						
min.	°C	-40				
max.	°C	+130				
ambient temperature						
min.	°C	-40				
max.	°C	+130				
temperature compensation		x				
explosion protection						
• TR TS						
order code		GSG-NE2TS/**	GSK-NE2TS/**	GSM-NE2TS/**	GSP-NE2TS/**	GSQ-NE2TS/**
technical type		GDG1N52	GDK1N52	GDM2N52	GDP2N52	GDQ2N52
marking		2Ex nA IIC T6...T3 Gc Ex tb IIIC T180 °C...T65 °C Db от -55 °C до +180 °C				
certification		EAC Ex TC RU C-DE.BH02.B.00644				



¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² shear wave transducer:

typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request

inner pipe diameter max. recommended/max. extended: in reflection arrangement and for a flow velocity of 15 m/s

Shear wave transducers (zone 2 - nonEx, TS, IP68)




order code		GSG-N**TS/IP68	GSK-N**TS/IP68	GSM-N**TS/IP68	GSP-N**TS/IP68
technical type		GDG1LI8	GDK1LI8	GDM2LI8	GDP2LI8
transducer frequency	MHz	0.2	0.5	1	2
fluid pressure ¹					
min. extended	bar	metal pipe: 20			
min.	bar	metal pipe: 30, plastic pipe: 1			
inner pipe diameter d ²					
min. extended	mm	180	60	30	15
min. recommended	mm	220	80	40	20
max. recommended	mm	900	300	150	50
max. extended	mm	1100	360	180	60
pipe wall thickness					
min.	mm	11	5	2.5	1.2
material					
housing		PEEK with stainless steel cover 316Ti (1.4571)			
contact surface		PEEK			
degree of protection		IP68 ³			
transducer cable					
type		2550			
length	m	12			
dimensions					
length l	mm	130		72	
width b	mm	54		32	
height h	mm	83.5		46	
dimensional drawing					
weight (without cable)	kg	0.43		0.085	
pipe surface temperature					
min.	°C	-40			
max.	°C	+100			
ambient temperature					
min.	°C	-40			
max.	°C	+100			
temperature compensation		x			
explosion protection					
• TR TS					
order code		GSG-NE2TS/IP68	GSK-NE2TS/IP68	-	-
marking		2Ex nA IIC T6...T5 Gc Ex tb IIIC T90 °C...75 °C Db от -40 °C до +90 °C			
certification		EAC Ex TC RU C-DE.BH02.B.00644		-	-

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² shear wave transducer:
typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request
inner pipe diameter max. recommended/max. extended: in reflection arrangement and for a flow velocity of 15 m/s

³ test conditions: 3 months/2 bar (20 m)/20 °C

Shear wave transducers (zone 2 - nonEx, TS, extended temperature range)

order code		GSG-ENNTS/**	GSK-ENNTS/**	GSM-E**TS/**	GSP-E**TS/**	GSQ-E**TS/**
technical type		G(DL)G1E52	G(DL)K1E52	G(DL)M2E52	G(DL)P2E52	G(DL)Q2E52
transducer frequency	MHz	0.2	0.5	1	2	4
fluid pressure ¹						
min. extended	bar	metal pipe: 20		metal pipe: 20		
min.	bar	metal pipe: 30, plastic pipe: 1		metal pipe: 30, plastic pipe: 1		
inner pipe diameter d ²						
min. extended	mm	180	60	30	15	7
min. recommended	mm	220	80	40	20	10
max. recommended	mm	900	300	150	50	22
max. extended	mm	1100	360	180	60	30
pipe wall thickness						
min.	mm	11	5	2.5	1.2	0.6
material						
housing		PPSU with stainless steel cover 304 (1.4301), ***-*****/OS: 316L (1.4404)		PI with stainless steel cover 304 (1.4301), ***-*****/OS: 316L (1.4404)		
contact surface		PPSU		PI		
degree of protection		IP65		IP56		
transducer cable						
type		1699		6111		
length	m	5		4		3
length (***-*****/LC)	m	9		9 (not for *L ***** with ***-E****)		
dimensions						
length l	mm	129.5		64		40
width b	mm	51		32		22
height h	mm	67		40.5		25.5
dimensional drawing						
weight (without cable)	kg	0.82		0.066		0.017
pipe surface temperature						
min.	°C	-40		-30		-30
max.	°C	+170		+240 ³		+200
ambient temperature						
min.	°C	-40		-30		-30
max.	°C	+170		+40 +60 ⁴ +200 ⁵		+200
temperature compensation		x		x		
explosion protection						
• TR TS						
order code		-	-	GSM-EE2TS/**	GSP-EE2TS/**	GSQ-EE2TS/**
technical type		-	-	GDM2E52	GDP2E52	GDQ2E52
marking		-	-	2Ex nA IIC T6...T2 Gc Ex tb IIIA T215 °C...65 °C Db от -45 °C до +225 °C ³		
certification		-	-	EAC Ex TC RU C-DE.BH02.B.00644		

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² shear wave transducer:

typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request

inner pipe diameter max. recommended/max. extended: in reflection arrangement and for a flow velocity of 15 m/s

³ > +200 °C:

Variofix C without cover or Variofix L


observe the insulation instruction

Ex: ambient temperature max. +40 °C

⁴ pipe surface temperature +200...+240 °C: Variofix C without cover

⁵ pipe surface temperature max. +200 °C

Shear wave transducers (zone 1, TS)



order code		GSG-N*1TS/**	GSK-N*1TS/**	GSM-N*1TS/**	GSP-N*1TS/**	GSQ-N*1TS/**
technical type		GDG1N81	GDK1N81	GDM2N81	GDP2N81	GDQ2N81
transducer frequency	MHz	0.2	0.5	1	2	4
fluid pressure ¹						
min. extended	bar	metal pipe: 20				
min.	bar	metal pipe: 30, plastic pipe: 1				
inner pipe diameter d ²						
min. extended	mm	180	60	30	15	7
min. recommended	mm	220	80	40	20	10
max. recommended	mm	900	300	150	50	22
max. extended	mm	1100	360	180	60	30
pipe wall thickness						
min.	mm	11	5	2.5	1.2	0.6
material						
housing		PEEK with stainless steel cover 304 (1.4301), ***-*****/OS: 316L (1.4404)				
contact surface		PEEK				
degree of protection		IP65	IP66			IP65
transducer cable						
type		1699				
length	m	5		4		3
dimensions						
length l	mm	129.5	126.5	64		40
width b	mm	51	51	32		22
height h	mm	67	67.5	40.5		25.5
dimensional drawing						
weight (without cable)	kg	0.47	0.36	0.066		0.016
pipe surface temperature						
min.	°C	-40				
max.	°C	+130				
ambient temperature						
min.	°C	-40				
max.	°C	+130				
temperature compensation		x				
explosion protection						
• TR TS						
order code		GSG-NE1TS/**	GSK-NE1TS/**	GSM-NE1TS/**	GSP-NE1TS/**	GSQ-NE1TS/**
marking		1Ex e q IIC T6...T3 Gb Ex tb IIIC T130 °C Db от -55 °C до +140 °C				
certification		EAC Ex TC RU C-DE.BH02.B.00644				

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air² shear wave transducer:

typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request

inner pipe diameter max. recommended/max. extended: in reflection arrangement and for a flow velocity of 15 m/s

Shear wave transducers (zone 1, TS, IP68)

order code		GSG-N*1TS/IP68	GSK-N*1TS/IP68	GSM-N*1TS/IP68	GSP-N*1TS/IP68
technical type		GDG1L11	GDK1L11	GDM2L11	GDP2L11
transducer frequency	MHz	0.2	0.5	1	2
fluid pressure ¹					
min. extended	bar	metal pipe: 20			
min.	bar	metal pipe: 30, plastic pipe: 1			
inner pipe diameter d ²					
min. extended	mm	180	60	30	15
min. recommended	mm	220	80	40	20
max. recommended	mm	900	300	150	50
max. extended	mm	1100	360	180	60
pipe wall thickness					
min.	mm	11	5	2.5	1.2
material					
housing		PEEK with stainless steel cover 316Ti (1.4571)			
contact surface		PEEK			
degree of protection		IP68 ³			
transducer cable					
type		2550			
length	m	12			
dimensions					
length l	mm	130		72	
width b	mm	54		32	
height h	mm	83.5		46	
dimensional drawing					
weight (without cable)	kg	0.43		0.085	
pipe surface temperature					
min.	°C	-40			
max.	°C	+100			
ambient temperature					
min.	°C	-40			
max.	°C	+100			
temperature compensation		x			
explosion protection					
• TR TS					
order code		GSG-NE1TS/IP68	GSK-NE1TS/IP68	GSM-NE1TS/IP68	GSP-NE1TS/IP68
marking		1Ex q IIC T6...T3 Gb Ex tb IIIC T130 °C Db от -40 °C до +80 °C			
certification		EAC Ex TC RU C-DE.BH02.B.00644			

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air




² shear wave transducer:

typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request

inner pipe diameter max. recommended/max. extended: in reflection arrangement and for a flow velocity of 15 m/s

³ test conditions: 3 months/2 bar (20 m)/20 °C

Shear wave transducers (zone 1, TS, extended temperature range)

order code		GSM-E*1TS/**	GSP-E*1TS/**	GSQ-E*1TS/**
technical type		GDM2E85	GDP2E85	GDQ2E85
transducer frequency	MHz	1	2	4
fluid pressure ¹				
min. extended	bar	metal pipe: 20		
min.	bar	metal pipe: 30, plastic pipe: 1		
inner pipe diameter d ²				
min. extended	mm	30	15	7
min. recommended	mm	40	20	10
max. recommended	mm	150	50	22
max. extended	mm	180	60	30
pipe wall thickness				
min.	mm	2.5	1.2	0.6
material				
housing		PI with stainless steel cover 304 (1.4301), ***-*****/OS: 316L (1.4404)		
contact surface		PI		
degree of protection		IP66		IP56
transducer cable				
type		6111		
length	m	4		3
dimensions				
length l	mm	64		40
width b	mm	32		22
height h	mm	40.5		25.5
dimensional drawing				
weight (without cable)	kg	0.066		0.017
pipe surface temperature				
min.	°C	-30		-30
max.	°C	+240 ³		+200
ambient temperature				
min.	°C	-30		-30
max.	°C	+40 +200 ⁴		+200
temperature compensation		x		
explosion protection				
• TR TS				
order code		GSM-EE1TS/**	GSP-EE1TS/**	GSQ-EE1TS/**
marking		1Ex e q IIC T6...T2 Gb Ex tb IIIA T215 °C...65 °C Db от -45 °C до +225 °C ³		
certification		 TC RU C-DE.BH02.B.00644		




¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² shear wave transducer:
typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request
inner pipe diameter max. recommended/max. extended: in reflection arrangement and for a flow velocity of 15 m/s

³ > +200 °C :
Variofix L or Variofix C
observe the insulation instruction
ambient temperature max. +40 °C

⁴ pipe surface temperature max. +200 °C



Lamb wave transducers (zone 2 - FM Class I Div. 2 - nonEx, TS)

order code		GLF-N**TS/**	GLG-N**TS/**	GLH-N**TS/**	GLK-N**TS/**	GLM-N**TS/**	GLP-N**TS/**	GLQ-N**TS/**
technical type		G(RT)F1N52	G(RT)G1N52	G(RT)H1N52	G(RT)K1N52	G(RT)M1N52	G(RT)P1N52	G(RT)Q1N52
transducer frequency	MHz	0.15	0.2	0.3	0.5	1	2	4
fluid pressure ¹								
min. extended	bar	metal pipe: 10			metal pipe: 10 (d > 120 mm) 3 (d < 120 mm)	metal pipe: 3 (d < 60 mm)	metal pipe: 3 (d < 35 mm)	metal pipe: 3 (d < 15 mm)
min.	bar	metal pipe: 15 plastic pipe: 1			metal pipe: 15 (d > 120 mm) 10 (d < 120 mm) plastic pipe: 1	metal pipe: 10 (d > 60 mm) 5 (d < 60 mm) plastic pipe: 1	metal pipe: 10 (d > 35 mm) 5 (d < 35 mm) plastic pipe: 1	metal pipe: 10 (d > 15 mm) 5 (d < 15 mm) plastic pipe: 1
inner pipe diameter d ²								
min. extended	mm	220	180	110	60	30	15	7
min. recommended	mm	270	220	140	80	40	20	10
max. recommended	mm	1200	900	600	300	150	50	22
max. extended	mm	1600	1400	1000	360	180	60	30
pipe wall thickness								
min.	mm	15	11	8	5	2.5	1.2	0.6
max.	mm	32	24	16	10	5	3	1.2
max. extended	mm	35	-	-	-	-	-	-
material								
housing		PPSU with stainless steel cover 316Ti (1.4571)	PPSU with stainless steel cover 304 (1.4301), ***-*****/OS: 316L (1.4404)					
contact surface		PPSU						
degree of protection		IP54	IP67	IP65				
transducer cable								
type		1699						
length	m	5	4					3
length (***-*****/LC)	m	9 (not for *T***** with ***-*E***)						
dimensions								
length l	mm	163	128.5	74			42	
width b	mm	54	51	32			22	
height h	mm	91.3	67.5	40.5			25.5	
dimensional drawing								
weight (without cable)	kg	0.935	0.471	0.077			0.019	
pipe surface temperature								
min.	°C	-40						
max.	°C	+130						
ambient temperature								
min.	°C	-40						
max.	°C	+130						
temperature compensation		x						
explosion protection								
• TR TS								
order code		GLF-NE2TS	GLG-NE2TS/**	GLH-NE2TS/**	GLK-NE2TS/**	GLM-NE2TS/**	GLP-NE2TS/**	GLQ-NE2TS/**
technical type		GRF1N52	GRG1N52	GRH1N52	GRK1N52	GRM1N52	GRP1N52	GRQ1N52
marking		2Ex nA IIC T6...T3 Gc Ex tb IIIC T180 °C...T65 °C Db от -55 °C до +150 °C						
certification		EAC Ex TC RU C-DE.BH02.B.00644						

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² Lamb wave transducer:
typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request
inner pipe diameter max. recommended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 15 m/s (30 m/s)
inner pipe diameter max. extended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 12 m/s (25 m/s)

Lamb wave transducers (zone 2 - nonEx, TS, IP68)




order code		GLF-N**TS/IP68	GLG-N**TS/IP68	GLH-N**TS/IP68	GLK-N**TS/IP68	GLM-N**TS/IP68	GLP-N**TS/IP68
technical type		GRF1LI8	GRG1LI8	GRH1LI8	GRK1LI8	GRM1LI8	GRP1LI8
transducer frequency	MHz	0.15	0.2	0.3	0.5	1	2
fluid pressure ¹							
min. extended	bar	metal pipe: 10			metal pipe: 10 (d > 120 mm) 3 (d < 120 mm)	metal pipe: 3 (d < 60 mm)	metal pipe: 3 (d < 35 mm)
min.	bar	metal pipe: 15 plastic pipe: 1			metal pipe: 15 (d > 120 mm) 10 (d < 120 mm) plastic pipe: 1	metal pipe: 10 (d > 60 mm) 5 (d < 60 mm) plastic pipe: 1	metal pipe: 10 (d > 35 mm) 5 (d < 35 mm) plastic pipe: 1
inner pipe diameter d ²							
min. extended	mm	220	180	110	60	30	15
min. recommended	mm	270	220	140	80	40	20
max. recommended	mm	1200	900	600	300	150	50
max. extended	mm	1600	1400	1000	360	180	60
pipe wall thickness							
min.	mm	15	11	8	5	2.5	1.2
max.	mm	32	24	16	10	5	3
max. extended	mm	35	-	-	-	-	-
material							
housing		PPSU with stainless steel cover 316Ti (1.4571)					
contact surface		PPSU					
degree of protection		IP68 ³					
transducer cable							
type		2550					
length	m	12					
dimensions							
length l	mm	173	143.5		73		
width b	mm	54	54		31.6		
height h	mm	91.5	83.5		46		
dimensional drawing							
weight (without cable)	kg	1.36	0.639		0.093		
pipe surface temperature							
min.	°C	-40					
max.	°C	+100					
ambient temperature							
min.	°C	-40					
max.	°C	+100					
temperature compensation		x					
explosion protection							
• TR TS							
order code		-	GLG-NE2TS/ IP68	GLH-NE2TS/ IP68	GLK-NE2TS/ IP68	GLM-NE2TS/ IP68	GLP-NE2TS/ IP68
marking		-	2Ex nA IIC T6...T5 Gc Ex tb IIIC T90 °C...75 °C Db от -40 °C до +90 °C				
certification		-	EAC Ex TC RU C-DE.BH02.B.00644				

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² Lamb wave transducer:
typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request
inner pipe diameter max. recommended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 15 m/s (30 m/s)
inner pipe diameter max. extended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 12 m/s (25 m/s)

³ test conditions: 3 months/2 bar (20 m)/20 °C

Lamb wave transducers (zone 1, TS)

order code		GLF-N*1TS/**	GLG-N*1TS/**	GLH-N*1TS/**	GLK-N*1TS/**	GLM-N*1TS/**	GLP-N*1TS/**	GLQ-N*1TS/**
technical type		GRF1N83	GRG1N83	GRH1N83	GRK1N83	GRM1N83	GRP1N83	GRQ1N83
transducer frequency	MHz	0.15	0.2	0.3	0.5	1	2	4
fluid pressure ¹								
min. extended	bar	metal pipe: 10			metal pipe: 10 (d > 120 mm) 3 (d < 120 mm)	metal pipe: 3 (d < 60 mm)	metal pipe: 3 (d < 35 mm)	metal pipe: 3 (d < 15 mm)
min.	bar	metal pipe: 15 plastic pipe: 1			metal pipe: 15 (d > 120 mm) 10 (d < 120 mm) plastic pipe: 1	metal pipe: 10 (d > 60 mm) 5 (d < 60 mm) plastic pipe: 1	metal pipe: 10 (d > 35 mm) 5 (d < 35 mm) plastic pipe: 1	metal pipe: 10 (d > 15 mm) 5 (d < 15 mm) plastic pipe: 1
inner pipe diameter d ²								
min. extended	mm	220	180	110	60	30	15	7
min. recommended	mm	270	220	140	80	40	20	10
max. recommended	mm	1200	900	600	300	150	50	22
max. extended	mm	1600	1400	1000	360	180	60	30
pipe wall thickness								
min.	mm	15	11	8	5	2.5	1.2	0.6
max.	mm	32	24	16	10	5	3	1.2
max. extended	mm	35	-	-	-	-	-	-
material								
housing		PPSU with stainless steel cover 304 (1.4301), ***-****/OS: 316L, 316Ti (1.4404, 1.4571)				PPSU with stainless steel cover 304 (1.4301), ***-****/OS: 316L (1.4404)		
contact surface		PPSU						
degree of protection		IP54		IP66		IP65		
transducer cable								
type		1699						
length	m	5				4		3
dimensions								
length l	mm	163	128.5			74		42
width b	mm	54	51			32		22
height h	mm	91.3	67.5			40.5		25.5
dimensional drawing								
weight (without cable)	kg	0.935	0.471			0.077		0.019
pipe surface temperature								
min.	°C	-40						
max.	°C	+130						
ambient temperature								
min.	°C	-40						
max.	°C	+130						
temperature compensation		x						
explosion protection								
• TR TS								
order code		GLF-NE1TS/**	GLG-NE1TS/**	GLH-NE1TS/**	GLK-NE1TS/**	GLM-NE1TS/**	GLP-NE1TS/**	GLQ-NE1TS/**
technical type		GRF1N83	GRG1N83	GRH1N83	GRK1N83	GRM1N83	GRP1N83	GRQ1N83
marking		1Ex e q IIC T6...T3 Gb Ex tb IIIC T130 °C Db от -55 °C до +140 °C						
certification		EAC Ex TC RU C-DE.BH02.B.00644						

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air



² Lamb wave transducer:

typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request

inner pipe diameter max. recommended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 15 m/s (30 m/s)

inner pipe diameter max. extended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 12 m/s (25 m/s)

Lamb wave transducers (zone 1, TS, IP68)

order code		GLG-N*1TS/IP68	GLH-N*1TS/IP68	GLK-N*1TS/IP68	GLM-N*1TS/IP68	GLP-N*1TS/IP68
technical type		GRG1LI3	GRH1LI3	GRK1LI3	GRM1LI3	GRP1LI3
transducer frequency	MHz	0.2	0.3	0.5	1	2
fluid pressure ¹						
min. extended	bar	metal pipe: 10		metal pipe: 10 (d > 120 mm) 3 (d < 120 mm)	metal pipe: 3 (d < 60 mm)	metal pipe: 3 (d < 35 mm)
min.	bar	metal pipe: 15 plastic pipe: 1		metal pipe: 15 (d > 120 mm) 10 (d < 120 mm) plastic pipe: 1	metal pipe: 10 (d > 60 mm) 5 (d < 60 mm) plastic pipe: 1	metal pipe: 10 (d > 35 mm) 5 (d < 35 mm) plastic pipe: 1
inner pipe diameter d ²						
min. extended	mm	180	110	60	30	15
min. recommended	mm	220	140	80	40	20
max. recommended	mm	900	600	300	150	50
max. extended	mm	1400	1000	360	180	60
pipe wall thickness						
min.	mm	11	8	5	2.5	1.2
max.	mm	24	16	10	5	3
material						
housing		PPSU with stainless steel cover 316Ti (1.4571)				
contact surface		PPSU				
degree of protection		IP68 ³				
transducer cable						
type		2550				
length	m	12				
dimensions						
length l	mm	143.5			73	
width b	mm	54			31.6	
height h	mm	83.5			46	
dimensional drawing						
weight (without cable)	kg	0.639			0.093	
pipe surface temperature						
min.	°C	-40				
max.	°C	+100				
ambient temperature						
min.	°C	-40				
max.	°C	+100				
temperature compensation		x				
explosion protection						
• TR TS						
order code		GLG-NE1TS/IP68	GLH-NE1TS/IP68	GLK-NE1TS/IP68	GLM-NE1TS/IP68	GLP-NE1TS/IP68
marking		1Ex q IIC T6...T3 Gb Ex tb IIIC T130 °C Db от -40 °C до +80 °C				
certification		EAC Ex TC RU C-DE.BH02.B.00644				

¹ depending on the application, typical absolute value for natural gas, nitrogen, compressed air

² Lamb wave transducer:

typical values for natural gas, nitrogen, oxygen; pipe diameters for other fluids on request

inner pipe diameter max. recommended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 15 m/s (30 m/s)




inner pipe diameter max. extended: in reflection arrangement (diagonal arrangement) and for a flow velocity of 12 m/s (25 m/s)

³ test conditions: 3 months/2 bar (20 m)/20 °C

Transducer mounting fixture

Order code

1, 2	3	4	5	6	7...9	no. of character
transducer mounting fixture	transducer	measurement arrangement	size	fixation	outer pipe diameter	option
VL						Variofix L
VC						Variofix C
	F					transducers with transducer frequency F
	K					transducers with transducer frequency G, H, K
	M					transducers with transducer frequency M, P
	Q					transducers with transducer frequency Q
		D				reflection arrangement or diagonal arrangement
		R				reflection arrangement
			S			small
			M			medium
			L			large
				B		bolts
				S		tension straps
				W		welding
				N		without fixation
					002	10...20 mm
					004	20...40 mm
					T36	40...360 mm
					013	10...130 mm
					036	130...360 mm
					092	360...920 mm
					200	920...2000 mm
						IP68 for transducers with degree of protection IP68
						OS housing with stainless steel 316
						Z special design

<p>Variofix L (VLK, VLM, VLQ)</p> 	<p>material: stainless steel 304 (1.4301), 301 (1.4310), 410 (1.4006) option OS: 316Ti (1.4571), 316L (1.4404), 17-7PH (1.4568) inner length: VLK: 348 mm, option IP68: 368 mm VLM: 234 mm VLQ: 176 mm dimensions: VLK: 423 x 90 x 93 mm option IP68: 443 x 94 x 105 mm VLM: 309 x 57 x 63 mm VLQ: 247 x 43 x 47 mm</p>
<p>Variofix L with bolt mounting plates (VL*-**-B)</p> 	<p>material: stainless steel 304 (1.4301), 301 (1.4310), 410 (1.4006) option OS: 316Ti (1.4571), 316L (1.4404), 17-7PH (1.4568) inner length: VLM: 234 mm VLQ: 176 mm dimensions: VLM: 309 x 57 x 63 mm VLQ: 247 x 43 x 47 mm outer pipe diameter: max. 48 mm</p>
<p>Variofix C (VC)</p> 	<p>material: stainless steel 316Ti (1.4571) inner length: VCF-*-L, VCK-*-L: 500 mm VCF-*-S, VCK-*-S: 350 mm VCM: 400 mm VCQ: 250 mm dimensions: VCF-*-L, VCK-*-L: 560 x 126 x 125 mm VCF-*-S, VCK-*-S: 410 x 126 x 125 mm VCM: 460 x 96 x 82 mm VCQ: 310 x 85 x 71 mm</p>

Coupling materials for transducers

	normal temperature range (4th character of transducer order code = N)		extended temperature range (4th character of transducer order code = E)		
	< 100 °C	< 170 °C	< 150 °C	< 200 °C	200...240 °C
< 24 h	coupling compound type N or coupling foil type VT	coupling compound type E or coupling foil type VT	coupling compound type E or coupling foil type VT	coupling compound type E or H or coupling foil type VT	coupling foil type TF
long time measurement	coupling foil type VT	coupling foil type VT	coupling foil type VT	coupling foil type VT	coupling foil type TF


type VT: fluid temperature 200 °C: min. 2 years

Technical data

type	ambient temperature °C
coupling compound type N	-30...+130
coupling compound type E	-30...+200
coupling compound type H	-30...+250
coupling foil type VT	-10...+200
coupling foil type TF	200...240

Damping material (optional)

Damping material will be used for the gas measurement to reduce acoustic noise influences on the measurement.



Damping mats


Damping mats will be used for the gas measurement to reduce acoustic noise influences on the measurement.

transducer damping mat

Transducer damping mats will be installed below the transducers.

pipe damping mat

Pipe damping mats will be installed if the sound propagation is disturbed at reflection points (e.g. flange, weld). Depending on the noise, the pipe damping mats will be installed at one or both sides of the transducer damping mat. If the local conditions are unknown, pipe damping mats should be installed.



Technical data

type		E30R4	E30R3
order code		ACC-PE-GNNN-/DPD2	ACC-PE-GNNN-/DPD1
width	mm	225	50
thickness	mm	0.7	
length (per roll)	m	10	
weight	kg/m ²	1.015	
ambient temperature	°C	-30...+80	
properties		self-adhesive	

Dimensioning

transducer		damping mat							
transducer mounting fixture	order code	type	number of layers	transducer damping mat			transducer damping mat + 2x pipe damping mat		
				max. installation length [mm]	number of rolls ¹		max. installation length [mm]	number of rolls ¹	
					standard ²	extended ²		standard	extended
VarioFix L									
VLK	GLG	E30R4	3	890	4	4	1830	9	12
	GSG		3		4	4		9	10
	GLH		2		2	3		4	7
	GLK		1		1	1		2	2
	GSK		1		1	1		2	2
VLK-**-****/IP68	GLG	E30R4	3	930	5	5	1910	10	13
	GSG		3		5	5		10	11
	GLH		2		2	3		5	7
	GLK		1		1	1		2	2
	GSK		1		1	1		2	2
VLM	GLM	E30R3	1	660	1	1	1360	2	2
	GSM		1		1	1		2	2
	GLP		1		1	1		1	1
	GSP		1		1	1		1	1
VLQ	GLQ	E30R3	1	540	1	1	1120	1	1
	GSQ		1		1	1		1	1
Variofix C									
VCF-*/L-****/IP68	GLF	E30R4	3	1160	6	6	2360	13	15
VCK-*/L	GLG	E30R4	3	1160	6	6	2360	11	14
VCK-*/L-****/IP68	GSG		3		6	6		11	12
	GLH		2		3	4		5	8
	GLK		1		1	1		2	2
	GSK		1		1	1		2	2
VCF-*/S-****/IP68	GLF	E30R4	3	860	4	4	1760	9	10
VCK-*/S	GLG	E30R4	3	860	4	4	1760	7	9
VCK-*/S-****/IP68	GSG		3		4	4		7	8
	GLH		2		2	3		4	5
	GLK		1		1	1		1	1
	GSK		1		1	1		1	1
VCM	GLM	E30R3	1	960	2	2	1960	3	3
	GSM		1		2	2		3	3
	GLP		1		1	1		1	1
	GSP		1		1	1		1	1
VCQ	GLQ	E30R3	1	660	1	1	1360	1	1
	GSQ		1		1	1		1	1

¹ calculation on the base of:

max. installation length (installation of one transducer mounting fixture per transducer in reflection arrangement) and
max. recommended pipe diameter (standard) or max. extended pipe diameter (extended)

² calculation of the number of rolls when both transducers are mounted in one transducer mounting fixture (reflection arrangement) or in diagonal arrangement: number of rolls/2 and round up to the nearest integer

Damping coat

For high temperatures it is recommended to apply the damping coat onto the pipe.

Technical data







order code	ACC-PE-GNNN-/DPL1
material	multipolymeric matrix/inorganic ceramic coating
packing drum	I 1
properties	heat resistant, inert

Observe installation instructions (TI_DampingCoat).

Dimensioning

transducer frequency	number of packing drums		
	outer pipe diameter		
	≤300 mm	≤500	≤700
F	3	4	5
G	2	3	4
H	2	2	3
K	2	2	-
M	2	-	-
P	1	-	-
Q	1	-	-

Connection systems

connection system TS		
connection with extension cable	direct connection	transducers technical type
<p>JB01</p> 		<p>*****8*</p>
<p>JB01, JBP2, JBP3</p> 		<p>****L*</p>
<p>JB02, JB03</p> 		<p>*****52</p>

Cable

transducer cable				
type		1699	2550	6111
weight	kg/m	0.094	0.035	0.092
ambient temperature	°C	-55...+200	-40...+100	-100...+225
properties			longitudinal watertight	
cable jacket				
material		PTFE	PUR	PFA
outer diameter	mm	2.9	5.2 ±0.2	2.7
thickness	mm	0.3	0.9	0.5
colour		brown	grey	white
shield		x	x	x
sheath				
material		stainless steel 304 (1.4301) option OS: 316Ti (1.4571)	-	stainless steel 304 (1.4301) option OS: 316Ti (1.4571)
outer diameter	mm	8	-	8

extension cable			
type		2615	5245
order code		ACC-PE- GNNN-/EXEXXXX	ACC-PE- GNNN-/EXA1XXX
weight	kg/m	0.18	0.38
ambient temperature	°C	-30...+70	-30...+70
properties		halogen free fire propagation test according to IEC 60332-1 combustion test according to IEC 60754-2	halogen free fire propagation test according to IEC 60332-1 combustion test according to IEC 60754-2
cable jacket			
material		PUR	PUR
outer diameter	mm	max. 12	max. 12
thickness	mm	2	2
colour		black	black
shield		x	x
sheath			
material		-	steel wire braid with copolymer sheath
outer diameter	mm	-	max. 15.5

XXX - cable length in m

Cable length

transducer frequency		F, G, H, K		M, P		Q		S	
connection system TS									
transducers technical type		x	l	x	l	x	l	x	l
*(DR)***8*	m	5	≤ 300	4	≤ 300	3	≤ 90	-	-
*(DR)***5*	m	5	≤ 300	4	≤ 300	3	≤ 90	2	≤ 40
option LC: *(LT)***5*	m	9	≤ 300	9	≤ 300	9	≤ 90	-	-
option IP68: ****LJ*	m	12	≤ 300	12	≤ 300	-	-	-	-

x - transducer cable length


l - max. length of extension cable (depending on the application)

Junction box

Technical data

JB01S4E3M, JBP2, JBP3		
weight	kg	1.2 kg
fixation		wall mounting optional: 2" pipe mounting
material		
housing		stainless steel 316L (1.4404)
gasket		silicone
degree of protection		IP67
ambient temperature		
min.	°C	-40
max.	°C	+80
explosion protection		
• TR TS (zone 1)		
junction box		JB01S4E3M
marking		1Ex e mb II T6...T4 Gb Ex tb IIIC 100°C Db T6: от -40 °C до +70 °C T4, T5: от -40 °C до +80 °C
certification		ERC Ex TC RU C-DE.BH02.B.00644
type of protection		gas: increased safety decoupled network: encapsulation dust: protection by enclosure
• TR TS (zone 2)		
junction box		JBP2
marking		2Ex nA IIC T6...T4 Gc Ex tc IIIC 80°C Dc T6: от -40 °C до +70 °C T4, T5: от -40 °C до +80 °C
certification		ERC Ex TC RU C-DE.BH02.B.00644

Connection




terminal strip	terminal	connection	transducer
KL1	V	signal	↑
	VS	internal shield	
	RS	internal shield	⤴
	R	signal	

Extension cable

terminal strip	terminal	connection
KL2	TV	signal
	TVS	internal shield
	TRS	internal shield
	TR	signal

JB02, JB03		
weight	kg	1.2 kg
fixation		wall mounting optional: 2" pipe mounting
material		
housing		stainless steel 316L (1.4404)
gasket		silicone
degree of protection		IP67
ambient temperature		
min.	°C	-40
max.	°C	+80
explosion protection		
• TR TS		
junction box		JB02
marking		2Ex nA IIC T6...T4 Gc Ex tc IIIC 80°C Dc T6: от -40 °C до +70 °C T4, T5: от -40 °C до +80 °C
certification		ERC Ex TC RU C-DE.BH02.B.00644

Connection




	terminal	connection	transducer
	XV	SMB connector	↑
	XR	SMB connector	


Extension cable

terminal strip	terminal	connection
KL2	TV	signal
	TVS	internal shield
	TRS	internal shield
	TR	signal

Dimensions







2" pipe mounting kit







Clamp-on temperature probe (optional)


Technical data




PT12N		
design		clamp-on with connector
type		Pt100
connection		4-wire
measuring range	°C	-30...+250
accuracy T		±(0.15 °C + 2 · 10 ⁻³ · T [°C]) class A
accuracy ΔT (2x Pt matched according to EN 1434-1)		≤ 0.1 K (3 K < ΔT < 6 K), more corresponding to EN 1434-1
response time	s	50
housing		aluminum
degree of protection		IP66
dimensions		
length l	mm	20
width b	mm	15
height h	mm	13
dimensional drawing		
weight	kg	0.25 (without connector)
accessories		
thermal conductivity paste 200 °C		x
thermal conductivity foil 250 °C		x

Connection system			
direct connection/connection with extension cable			
			
Connection			
	temperature probe	extension cable	connector
	red	grey	2
	red/blue	red	6
	white/blue	blue	1
	white	white	7
			
Cable			
	temperature probe	extension cable	
type	4 x 0.25 mm² black	LIYCY 8 x 0.14 mm² grey	
standard length	m	3	
max. length	m	-	
cable jacket	PTFE	PVC	


PT12N		
design		clamp-on nonEx or TR TS
type		Pt100
connection		4-wire
measuring range	°C	-30...+250
accuracy T		±(0.15 °C + 2 · 10 ⁻³ · T [°C]) class A
accuracy ΔT (2x Pt matched according to EN 1434-1)		≤ 0.1 K (3 K < ΔT < 6 K), more corresponding to EN 1434-1
response time	s	50
housing		aluminum
degree of protection		IP66
dimensions		
length l	mm	20
width b	mm	15
height h	mm	13
dimensional drawing		
weight	kg	0.25
accessories		
thermal conductivity foil 250 °C		x
explosion protection (optional)		
• TR TS		
marking		2Ex nA IIC T6...T2 Gc от -30°C до +250 °C
certification		ERC Ex RU C-DE.BH02.B.00644




Connection system		
connection with extension cable	direct connection	
		
junction box		
Connection		
	temperature probe	
	red	
	red/blue	
	white/blue	
	white	
Cable		
	temperature probe	extension cable
type	4 x 0.25 mm² black	LIYCY 8 x 0.14 mm² grey
standard length	m	3
max. length	m	-
cable jacket	PTFE	PVC

PT12F			
design		clamp-on short response time, with connector	
type		Pt100	
connection		4-wire	
measuring range	°C	-50...+250	
accuracy T		±(0.15 °C + 2 · 10 ⁻³ · T [°C]) class A	
accuracy ΔT (2x Pt matched according to EN 1434-1)		≤ 0.1 K (3 K < ΔT < 6 K), more corresponding to EN 1434-1	
response time	s	8	
housing		PEEK, stainless steel 304 (1.4301), copper	
degree of protection		IP66	
dimensions			
length l	mm	14	
width b	mm	30	
height h	mm	27	
dimensional drawing			
weight	kg	0.32 (without connector)	
accessories			
thermal conductivity paste 200 °C		x	
thermal conductivity foil 250 °C		x	
plastic protection plate, insulation foam		x	


Connection system			
			
Connection			
	temperature probe	extension cable	connector
	red	grey	2
	red/blue	red	6
	white/blue	blue	1
	white	white	7
			



Cable			
		temperature probe	extension cable
type		4 x 0.25 mm² black	LIYCY 8 x 0.14 mm² grey
standard length	m	3	5/10/25
max. length	m	-	200
cable jacket		PTFE	PVC


PT12F			
design		clamp-on short response time	
type		Pt100	
connection		4-wire	
measuring range	°C	-50...+250	
accuracy T		±(0.15 °C + 2 · 10 ⁻³ · T [°C]) class A	
response time	s	8	
housing		PEEK, stainless steel 304 (1.4301), copper	
degree of protection		IP66	
dimensions			
length l	mm	14	
width b	mm	30	
height h	mm	27	
dimensional drawing			
weight	kg	0.32	
accessories			
thermal conductivity paste 200 °C		x	
thermal conductivity foil 250 °C		x	
plastic protection plate, insulation foam		x	

Connection system		
connection with extension cable		direct connection
		
Connection		
	temperature probe	
	red	
	red/blue	
	white/blue	
	white	

Cable		
	temperature probe	extension cable
type	4 x 0.25 mm² black	LIYCY 8 x 0.14 mm² grey
standard length	m	3
max. length	m	-
cable jacket		PTFE



PT12F		
design		clamp-on short response time
type		Pt100
connection		4-wire
measuring range	°C	-50...+250
accuracy T		$\pm(0.15\text{ °C} + 2 \cdot 10^{-3} \cdot T\text{ [°C]})$ class A
response time	s	8
housing		PEEK, stainless steel 304 (1.4301), copper
degree of protection		IP66
dimensions		
length l	mm	14
width b	mm	30
height h	mm	27
dimensional drawing		
weight	kg	0.32
accessories		
thermal conductivity paste 200 °C	x	
thermal conductivity foil 250 °C	x	
plastic protection plate, insulation foam	x	

Connection system		
connection with extension cable		direct connection
		

Connection	
	temperature probe
	red
	red/blue
	white/blue
	white

Cable		
	temperature probe	extension cable
type	4 x 0.25 mm² black	LIYCY 8 x 0.14 mm² grey
standard length	m 3	5/10/25
max. length	m -	200
cable jacket	PTFE	PVC


Fixation

tension strap PT12N 	material: stainless steel 301 (1.4310), 410 (1.4006) thermal insulation necessary
ball chain PT12F 	material: stainless steel 316L (1.4404) length: 1 m

Junction box

JBT2, JBT3		
order code		<ul style="list-style-type: none">• JBT2: ACC-PE-GNNN-/JB5• JBT3: ACC-PE-GNNN-/JB6
weight	kg	1.2 kg
fixation		wall mounting optional: 2" pipe mounting
material		
housing		stainless steel 316L (1.4404)
gasket		silicone
degree of protection		IP67
ambient temperature		
min.	°C	-40
max.	°C	+80
explosion protection		
• TR TS		
junction box		JBT2
marking		2Ex nA IIC T6...T4 Gc Ex tc IIIC 80°C Dc T6: от -40 °C до +70 °C T4, T5: от -40 °C до +80 °C
certification		EAC Ex TC RU C-DE.BH02.B.00644

Connection




The diagram shows a rectangular junction box with four mounting holes at the corners. Inside, there are two terminal strips labeled KL2 and KL1. KL2 has four terminals with symbols for red, red/blue, white, and white/blue. KL1 has four terminals with symbols for red, red/blue, white, and white/blue. Below the terminal strips is a temperature probe connection with two terminals, each marked with a plus sign (+).

terminal strip	terminal	connection
KL1	1	red
	2	red/blue
	3	white
	4	white/blue

Temperature probe

terminal strip	terminal	connection
KL2	1	red
	2	grey
	3	white
	4	blue

Dimensions



2" pipe mounting kit



FLEXIM GmbH
Boxberger Str. 4
12681 Berlin
Germany
Tel.: +49 (30) 93 66 76 60
Fax: +49 (30) 93 66 76 80
internet: www.flexim.com
e-mail: info@flexim.com

Subject to change without prior notice.
Errors excepted.

FLUXUS is a registered trademark of FLEXIM GmbH.

Copyright (©) FLEXIM GmbH 2020